



Country Ref.: B1250186409  
EAN 13: 8054803096120

### CONTACT

Market information  
industryprojects.business@lyn  
xeogroup.com

UL - listed control cables for fixed installation outside and inside cable tray and wind turbines, PVC jacket, unshielded, oil resistant, flame retardant, TC - ER and MTW approved, UL Listed

### STANDARDS

Product UL 1277; UL 2277; UL and CSA approval

Cables designed for static application, .

Applications:

- Machine tools
- Wood machines
- Marble working machines
- Robotics
- Industrial sector

Approvals:

UL MTW UL1063

UL TC - ER 90 ° C 600V UL1277

UL WTTC 90 ° C 1000V UL2277

UL DP - 1

UL AWM 600V UL758

C(UL) CIC/TC

## CHARACTERISTICS

18G2,5

Insulation colour

Black w. number + yellow/green

Sheath colour

2.5 mm<sup>2</sup>

18

18.3 mm

Copper content

432 kg/km

( )

682 kg/km



Operating temp.  
-5 ... 90 ° C



UL 1581 SEC. 1160 AND CSA FT4



Oil resistance  
Yes

Rated Voltage Uo/U	600 V 2000 V
Field of application 操作度范	Fixed installations - 5 ... 90 ° C
Minimum bending radius, static (XD)	15 UL 1581 SEC. 1160 AND CSA FT4
Oil resistance	Yes



Operating temp.  
- 5 ... 90 ° C



UL 1581 SEC. 1160 AND CSA FT4



Oil resistance  
Yes